

FOR AREA SPORTSMAN CARS LEGAL AT DELLS, ELKO, SLINGER, JEFFERSON, TOMAH,

As Sportsman style rules vary greatly track by track, Mid-Am reserves the right to adjust rules regarding visiting Area Sportsman cars for fair competition. If your car is deemed to have parts or alterations that Mid-Am determines are outside of the normal scope of Area Sportsman rules or do not represent what Mid-Am defines as Sportsman Racing, you may not be allowed to compete, or you may be mandated an additional weight penalty

AREA SPORTSMAN CARS ARE LIMITED TO TEMPORARY MEMBERSHIPS ONLY, AND MUST BE REGISTERED TO COMPETE. NO EXCEPTIONS IN 2025

CAR EXCLUSIONS FROM MID-AM:

- Mid-Am does not have enough data to guide an AS LSW engine program at this time.
- Mid-Am does not permit cars that are 116" or larger
- Mid-Am does not permit cars with a track width larger than 63.5"
- Mid-Am does not permit laid-back or offset cages
- Mid-Am does not permit Chromoly or any other exotic materials allowed in cages
- Mid-Am does not permit titanium or any other exotic materials allowed in engines
- Mid-Am does not permit rear shelves raised more than 1 inch.

WHERE MID-AM RULES SUPERSEDE YOUR LOCAL RULES:

• K.I.S.S. PRINCIPLE WILL APPLY

- All Mid-Am safety rules in its entirety in section 4
- All Mid-Am fuel cell rules in sections 5.0-5.4
- All Mid-Am spring/shock/shock tech rules in section 5.7
- All Mid-Am rear-end rules in section 5.16
- All Mid-Am wheel, tire, and spacer rules 6.7
- Fuel Burn off: ½ pound per lap on Raceways below 1/2 mile in size and 1 pound per lap on 1/2 mile and larger/ Road Courses

WEIGHTS:

- **3000# GM 602 CRATE MOTOR WITH GAUGE LEGAL 650 4 BBL**
- **3100# OPEN MOTOR WITH GAUGE LEGAL HOLLEY 4412 CARB**
- **MIN FRONT 52%, MAX LEFT 58% OF TOTAL**
 - +75# Clutchless/Brinn Transmission allowed for 602 Crate engine cars only
 - +50# For clutch smaller than 10.5". 7.25 diameter, two disk minimum.
 - +50# for crankshafts weighing less than 44 lbs.
 - +25# for headers (excludes 602) maximum of 1.625". No stepped, 180 degree or Tri-Y
 - +50# for 4779 carb (does not apply to 602)
 - -30# for metric style brakes

TRACK WIDTH/RIDE HEIGHT

- 63 1/2" tread width max
- Minimum Ride Height is 4 3/4"

MISC:

- One 5" by 60" spoiler allowed